


OUTDOOR SCOREBOARD
8341LS
Line Score Baseball



OVERALL DIMENSION	8' high x 32' wide x 4.75" deep.
INFORMATION DISPLAYED	Home Line Score, Guest Line Score, Ball, Strike, Out, Runs, Hits, Errors, At Bat, Hit, Error Indicators, Pitch Speed
DIGITS	Bright Red, 7-Segment LEDs.
SCORING	16" High Digits, Inning shall register 0-9. Runs shall register 0-99.
HITS	16" High Digits, Shall register 0-99.
ERRORS	16" High Digits, Shall register 0-9.
BALL	21" High Digits, Shall Register 1-3.
STRIKE	21" High Digits, Shall Register 1-2.
OUT	21" High Digits, Shall Register 1-2.
AT BAT	21" High Digits, Shall register 0-99.
HIT or ERROR	4" Bulls Eye, Displays on or off.
PITCH SPEED	21" High Digits, Shall register 0-199. Ability to manually enter a pitch speed or automatically display the pitch speed by connecting directly to a supported radar gun via hardwire cable or radio transmitter. Radar gun and accessories sold separately.
LED CAPTIONS	12" High Team Name, 16x80 LED Matrix (each), programmable from console.
CAPTIONS	White vinyl letters.
CONSTRUCTION	4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black, Navy, Blue, Bright Blue, Purple, Maroon, Red, Forest Green, Green, custom colors available).
ELECTRONICS	100% solid state, microprocessor controlled system.
SERVICING	Front access for ease of servicing. Plug in modules for ease of replacement.
MICROPROCESSOR CONTROL CONSOLE	Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available.
JUNCTION BOX	One junction box 5" x 3" with cover and plug. (Hardwire)
DATA CABLE	Twisted pair, direct burial, RJ45.
POWER REQUIREMENTS	115 VAC, 60 Hz. Minimum one 20A circuit is recommended.
INSTALLATION	May be installed on three posts. Mounting brackets are supplied with scoreboard.
WEIGHT	Net 1200 lbs. / Shipping 1800 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.

