


|  |   |
|--|---|
| <b>OUTDOOR SCOREBOARD<br/>         8425 FOOTBALL</b> |   |
| <b>OVERALL DIMENSION</b>                             | 8' high x 25' wide x 4.75" deep.  |
| <b>INFORMATION DISPLAYED</b>                         | Game Time, Home Score, Guest Score, Time Outs Left, Down, To Go, Ball On, Quarter   |
| <b>DIGITS</b>  | Bright Red, 7-Segment LEDs  |
| <b>TIMER</b>   | 24" High Digits, Shall register 0:00 - 99:59  |
| <b>SCORING</b>                                       | 24" High Digits, Shall register 0-99.   |
| <b>QUARTER</b>                                       | 24" High Digits, Shall register 1-4.  |
| <b>DOWN</b>  | 24" High Digits, Shall register 1-4.  |
| <b>TO GO</b>   | 24" High Digits, Shall register 1-99.   |
| <b>BALL ON</b>                                       | 24" High Digits, Shall register 1-99.   |
| <b>TIME OUTS LEFT</b>                                | 18" High Digits, Shall register 0-9.  |
| <b>POSSESSION</b>                                    | 4" Red LED Bullseye indicators.   |
| <b>CAPTIONS</b>                                      | White vinyl captions.   |
| <b>CONSTRUCTION</b>                                  | 4" extruded aluminum case, .093" thick. Face panels are 22 GA Galvaneal, finished in choice of colors (Black,Navy, Blue, Bright Blue, Violet, Maroon, Red, Dark Green, Green, custom colors available).   |
| <b>ELECTRONICS</b>                                   | 100% solid state, microprocessor controlled system.   |
| <b>SERVICING</b>                                     | Front access for ease of servicing. Plug in modules for ease of replacement.  |
| <b>MICROPROCESSOR CONTROL CONSOLE</b>                | Extruded Aluminum, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 13.25" wide x 5" high x 9" deep. Weights: 6 lbs. Microprocessor to be supplied with 25 feet of cable (hardwire). Microprocessor control console with membrane keyboard provides for direct entry of all information. Radio Control is available. |
| <b>JUNCTION BOX</b>                                  | One junction box 5" x 3" with cover and plug. (Hardwire)  |
| <b>DATA CABLE</b>                                    | Two (2) twisted pair, direct burial.  |
| <b>POWER REQUIREMENTS</b>                            | 120VAC. One 20A circuit is recommended.   |
| <b>INSTALLATION</b>                                  | May be installed on two posts. Mounting brackets are supplied with scoreboard.  |
| <b>WEIGHT</b>  | Net 680 lbs. / Shipping 820 lbs.  |
| <b>WARRANTY</b>                                      | Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label.  |