


<p><b>SCOREBOARD</b> <b>MP-5606</b> Volleyball</p>	
<b>OVERALL DIMENSION</b>	2'6" high x 6'1.75" wide x 6" deep.
<b>INFORMATION DISPLAYED</b>	Time in Minutes and Seconds, Home Score, Guest Score, Games Won
<b>DIGITS</b>	10" High LED Cluster Digits.
<b>ELECTRONICS</b>	100% Solid State, Microprocessor Controlled System.
<b>SCORING</b>	Shall register 0-99.
<b>TIMING</b>	Displayed by 4 digits with the capability of indicating 99:59. Instantly resetable to any time. Ascending or descending timing mode.
<b>GAMES</b>	Shall register 0-9.
<b>HORN</b>	Optional resonating horn enclosed in scoreboard. Automatically sounds at end of each timing period in descending mode, or may be operated manually at any time.
<b>CAPTIONS</b>	All captions will be white copy. Home, and Guest shall be 6" high. Games will be 3" high.
<b>CONSTRUCTION</b>	6" extruded aluminum case, .078" thick. Face panels are .050 Aluminum finished in choice of seven standard colors (Black, Blue, Red, Green, Navy, Purple and Maroon). Other colors are available at an additional cost.
<b>SERVICING</b>	Front access for ease of servicing. Plug in modules for ease of replacement.
<b>MICROPROCESSOR CONTROL CONSOLE</b>	Molded, high impact low profile microprocessor control console, latest state of the art, user friendly. Size: 17" wide x 8.625" high x 2.75" deep. Weight: 3 lbs. Hardwire models supplied with 25 feet of twisted pair, shielded direct burial data cable and junction Box. Microprocessor control console with membrane keyboard provides for direct entry of all information. Interchangeable keyboard inserts for ease of timing and scoring different sports, utilizing one 8000 series control console. LCD Monitor to display time and recall data displayed on scoreboard. Internal one minute time out timer, displayed on LCD Monitor with automatic audio at end of one minute period. Power on/off switch.
<b>UL &amp; NRTL APPROVED</b>	Meets FCC Class A Requirements.
<b>POWER REQUIREMENTS</b>	Scoreboard requires 1.5 amps, 120 volts, 60 hertz, recommend 1-15 amp circuit.
<b>INSTALLATION</b>	May be installed permanently by bolting to the wall with 1/2" hardware (not supplied).
<b>WEIGHT</b>	Net 112 lbs. Shipping 200 lbs.
<b>WARRANTY</b>	Five year guarantee against defects in material and workmanship. Factory exchange service for parts. Union Label.