



Choose 2
Available Options:

AT BAT
39
At Bat (AB)

HIT/ERROR
66
Hit/Error (HE)

EAGLES
Graphics (G)

PITCH COUNT
102
Pitch Count (PC)


PITCH SPEED
102 MPH
Pitch Speed (PS)

AT BAT 39	BALL 3		STRIKE 2		OUT 2		HIT/ERROR 66						
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

OUTDOOR SCOREBOARD
BA9220 + 2 OPTIONS

BA9220 + LEFT OPTION + RIGHT OPTION

STANDARD COLORS (CUSTOM COLORS AVAILABLE)



OVERALL DIMENSION

8' High x 22' Wide x 5" Depth. Additional 1.5" mounting flange on top and bottom. Style available in other sizes.

CONSTRUCTION

Fabricated 20 and 22 GA Powder Coated Galvanneal. 2 Cabinet Installation.

INFORMATION

Home & Guest 10 Inning Line Score (14"). Runs, Hits, Errors (14") Ball, Strike, Out (18"), Two Additional Options (Graphics or 18" Digits)

CAPTIONS

White vinyl captions: Home, Guest (8"). Innings, R, H, E (6.5"). Ball, Strike, Out (8").

HORN

Not Included. Optional 100dB or 110 dB horn available. Recommended to be wired at time of manufacture.

ELECTRONICS / DIGITS

100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red LED digits.

SERVICING

Sign will be serviceable by removing the home runs face to access components.

COMMUNICATION

Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.

POWER REQUIREMENTS

120VAC, 3.9 to 5.2 Amp. Installer to provide connection point or junction box to scoreboard. 20 Amp circuit recommended.

INSTALLATION

May be mounted to nearly any wall surface or a minimum of 2 posts/beams. Number and size of beams is dependent on soil condition and IBC wind loading requirements. Hardware supplied to mount by drilling through the scoreboard flange and I-beam. Pressure and additional clamping systems available. Pole/beam installations require supplied mounting bar on flange.

ESTIMATED WEIGHT

Approximately 685 lbs.

WARRANTY

Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union Label. UL Certified.

ADDITIONAL OPTIONS

MODEL NUMBER + () + ()

Hit/Error(HE), At Bat(AB), Graphics Area (G), Pitch Count(PC), Home and Guest Pitch Count (PC2), Pitch Speed(PS). Each option to display on either side of Ball Strike Out. Protective Lens Kit (PLK + Model Number). White, Green, Amber digits available (Red is standard).

AVAILABLE CONTROL CONSOLE

(SOLD SEPARATELY)

MSC9000 (Multi-sport Desktop Console) Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep. Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option included. Internal rechargeable battery. Switch between multiple sports by removing and replacing the slip sheet.


BA9220ABHE

Too many options? See the BA9220 Spec Sheet.

PRODUCT SPECIFICATIONS
BA9220 + 2 OPTIONS

ALL AMERICAN
SCOREBOARDS TM

BA9220ABG
 18" AT BAT (AB) digits on left.
 3'x5'6" Graphics Area on the right.

AT BAT	BALL	STRIKE	OUT													
39	3	2	2	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0								4	6	1
HOME	0	1	0	2	2									5	8	

BA9220ABHE
 18" AT BAT (AB) digits on left.
 18" HIT/ERROR (HE) digits on right.

AT BAT	BALL	STRIKE	OUT	HIT/ERROR													
39	3	2	2	EE	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0								4	6	1	
HOME	0	1	0	2	2									5	8		


BA9220ABPC
 18" AT BAT (AB) digits on left.
 18" PITCH COUNT (PC) digits (up to 199) on right. Pitch count toggles between teams.

AT BAT	BALL	STRIKE	OUT	PITCH COUNT													
39	3	2	2	102	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0								4	6	1	
HOME	0	1	0	2	2									5	8		

BA9220ABPS
 18" AT BAT (AB) digits on left.
 18" PITCH SPEED (PS) digits (up to 199) on right. Radar Gun sold seperately.

AT BAT	BALL	STRIKE	OUT	PITCH SPEED													
39	3	2	2	102 MPH	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0								4	6	1	
HOME	0	1	0	2	2									5	8		

BA9220GHE
 3'x5'6" Graphics Area on the left.
 18" HIT/ERROR (HE) on right.

				BALL	STRIKE	OUT	HIT/ERROR													
				3	2	2	EE	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST				0	3	0	1	0	0							4	6	1		
HOME				0	1	0	2	2								5	8			

PRODUCT SPECIFICATIONS
BA9220 + 2 OPTIONS

ALL AMERICAN


SCOREBOARDS

TM

BA9220GPC

3'x5'6" Graphics Area on the left.


18" PITCH COUNT (PC) digits (up to 199) on right. Pitch count toggles between teams.

	BALL			STRIKE			OUT			PITCH COUNT			
	3	2	2	102									
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

BA9220GPS


3'x5'6" Graphics Area on the left.

18" PITCH SPEED (PS) digits (up to 199) on right. Radar Gun sold separately.

	BALL			STRIKE			OUT			PITCH SPEED			
	3	2	2	102									
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

BA9220G2

Two 3'x5'6" Graphics Areas on the right and left sides.

	BALL			STRIKE			OUT			EAGLES			
	3	2	2										
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

BA9220PC2

18" PITCH COUNT for Home and Guest (PC2) digits (up to 199) on both sides of Ball Strike Out.

HOME	BALL			STRIKE			OUT			GUEST			
93	3	2	2	102									
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

BA9220PCHE

18" PITCH COUNT (PC) digits (up to 199) on left. Pitch count toggles between teams.

18" HIT/ERROR (HE) on right.

PITCH COUNT			BALL			STRIKE			OUT			HIT/ERROR		
102	3	2	2	66										
	1	2	3	4	5	6	7	8	9	10	R	H	E	
GUEST	0	3	0	1	0	0					4	6	1	
HOME	0	1	0	2	2						5	8		

PRODUCT SPECIFICATIONS
BA9220 + 2 OPTIONS

BA9220PCPS

18" PITCH COUNT (PC) digits (up to 199) on left. Pitch count toggles between teams.

18" PITCH SPEED (PS) digits (up to 199) on right. Radar Gun sold separately.

	PITCH COUNT			BALL	STRIKE	OUT	PITCH SPEED						
	100			3	2	2	102 MPH						
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

BA9220PSHE

18" PITCH SPEED (PS) digits (up to 199) on left. Radar Gun sold separately.

18" HIT/ERROR (HE) digits on right.

	PITCH SPEED			BALL	STRIKE	OUT	HIT/ERROR						
	102 MPH			3	2	2	E6						
	1	2	3	4	5	6	7	8	9	10	R	H	E
GUEST	0	3	0	1	0	0					4	6	1
HOME	0	1	0	2	2						5	8	

PLK + Model Number

Protective lenses installed in front of each digit assembly.

