



Available Options:

<b>AT BAT</b> 39 BA9240AB	<b>HIT/ERROR</b> E9 BA9240HE	<b>PITCH COUNT</b> 102 BA9240PC	<b>MPH</b> 102 BA9240PS
------------------------------	---------------------------------	------------------------------------	----------------------------

<b>BALL</b> 3	<b>STRIKE</b> 2	<b>OUT</b> 2			
	1 2 3 4 5	6 7 8 9 10	R	H	E
<b>GUEST</b>	0 3 0 1 0 0		4	6	1
<b>HOME</b>	0 1 0 2 2		5	8	

ALL AMERICAN

For more options, consider BA9240-2

<b>OVERALL DIMENSION</b>	8' High x 24' Wide x 5" Depth. Additional 1.5" mounting flange on top and bottom. Style available in other sizes.
<b>CONSTRUCTION</b>	Fabricated 20 and 22 GA Powder Coated Galvanneal. 2 Cabinet Installation.
<b>INFORMATION</b>	Home & Guest 10 Inning Line Score (14"). Runs, Hits, Errors (14") Hits, Ball, Strike, Out (18").
<b>CAPTIONS</b>	White vinyl captions: Home, Guest (8"). Innings, R, H, E (6.5"). Ball, Strike, Out (8"). Available graphic area of approx. 3'x6' (Standard on Base Model Only).
<b>HORN</b>	Not Included. Optional 100dB or 110 dB horn available. Recommended to be wired at time of manufacture.
<b>ELECTRONICS / DIGITS</b>	100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red LED digits.
<b>SERVICING</b>	Sign will be serviceable by removing the home runs face to access components.
<b>COMMUNICATION</b>	Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.
<b>POWER REQUIREMENTS</b>	120VAC, 3.9 Amp. Installer to provide connection point or junction box to scoreboard. 20 Amp circuit recommended.
<b>INSTALLATION</b>	May be mounted to nearly any wall surface or a minimum of 2 posts/beams. Number and size of beams is dependent on soil condition and IBC wind loading requirements. Hardware supplied to mount by drilling through the scoreboard flange and I-beam. Pressure and additional clamping systems available. Pole/beam installations require supplied mounting bar on flange.
<b>ESTIMATED WEIGHT</b>	747 lbs.
<b>WARRANTY</b>	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.
<b>ADDITIONAL OPTIONS</b> MODEL NUMBER + ( )	Hit/Error (HE), At Bat (AB), Pitch Count (PC), Pitch Speed (PS) in place of the Graphics Area. Protective Lens Kit (PLK + Model Number). White, Green, Amber digits available (Red is standard).
<b>AVAILABLE CONTROL CONSOLE</b> (SOLD SEPARATELY)	<b>MSC9000 (Multi-sport Desktop Console)</b> Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep. Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option included. Internal rechargeable battery. Switch between multiple sports by removing and replacing the slip sheet.

PRODUCT SPECIFICATIONS  
**BA9240 OPTIONS**

**BA9240AB**

18" AT BAT (AB) digits in place of graphics.

<b>BALL</b>	3	<b>STRIKE</b>	2	<b>OUT</b>	2					<b>AT BAT</b>	39		
	1	2	3	4	5	6	7	8	9	10	R	H	E
<b>GUEST</b>	0	3	0	1	0	0					4	6	1
<b>HOME</b>	0	1	0	2	2						5	8	

**BA9240HE**

18" HIT/ERROR (HE) digits in place of graphics.

<b>BALL</b>	3	<b>STRIKE</b>	2	<b>OUT</b>	2					<b>HIT/</b>	9		
	1	2	3	4	5	6	7	8	9	10	R	H	E
<b>GUEST</b>	0	3	0	1	0	0					4	6	1
<b>HOME</b>	0	1	0	2	2						5	8	

**BA9240PC**

18" PITCH COUNT (PC) digits (up to 199) in place of graphics. Pitch count toggles between teams.

<b>BALL</b>	3	<b>STRIKE</b>	2	<b>OUT</b>	2					<b>PITCH</b>	102		
	1	2	3	4	5	6	7	8	9	10	R	H	E
<b>GUEST</b>	0	3	0	1	0	0					4	6	1
<b>HOME</b>	0	1	0	2	2						5	8	

**BA9240PS**

18" PITCH SPEED (PS) digits (up to 199) in place of graphics.

<b>BALL</b>	3	<b>STRIKE</b>	2	<b>OUT</b>	2					<b>MPH</b>	102		
	1	2	3	4	5	6	7	8	9	10	R	H	E
<b>GUEST</b>	0	3	0	1	0	0					4	6	1
<b>HOME</b>	0	1	0	2	2						5	8	

**PLK + MODEL NUMBER**

Protective Lenses Installed in front of each digit assembly.

