




OUTDOOR SCOREBOARD
BA9280

STANDARD COLORS (CUSTOM COLORS AVAILABLE)
BLACK NAVY BLUE LIGHT BLUE PURPLE BURGUNDY RED FOREST GREEN GREEN

Available Options:

AT BAT 22 P H E	HIT/ERR 22 P H E	PITCH COUNT 01 P H E	PITCH SPEED 01 MPH P H E
BA9280AB	BA9280HE	BA9280PC	BA9280PS

BALL 3	STRIKE 2	OUT 2	EAGLES 													
	1 2 3 4 5 6 7 8 9 10												R	H	E	
GUEST	0	3	0	1	0	0								4	6	
HOME	0	1	0	2	2									5	8	

ALL AMERICAN SCOREBOARDS

For more options, consider BA9280-2

OVERALL DIMENSION	8' High x 28' Wide x 5" Depth. Additional 1.5" mounting flange on top and bottom. Style available in other sizes.
CONSTRUCTION	Fabricated 20 and 22 GA Powder Coated Galvanneal. 2 Cabinet Installation.
INFORMATION	Home & Guest 10 Inning Line Score (14"). Runs, Hits, Errors (14") Ball, Strike, Out (18").
CAPTIONS	White vinyl captions: Home, Guest (10"). Innings, R, H, E (8"). Ball, Strike, Out (10"). Available graphic area approx. 3'x10' (Standard on Base Model Only).
HORN	Not Included. Optional 100dB or 110 dB horn available. Recommended to be wired at time of manufacture.
ELECTRONICS / DIGITS	100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red LED digits.
SERVICING	Sign will be serviceable by removing the home runs face to access components.
COMMUNICATION	Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.
POWER REQUIREMENTS	120VAC, 5.2 Amp. Installer to provide connection point or junction box to scoreboard. 20 Amp circuit recommended.
INSTALLATION	May be mounted to nearly any wall surface or a minimum of 2 posts/beams. Number and size of beams is dependent on soil condition and IBC wind loading requirements. Hardware supplied to mount by drilling through the scoreboard flange and I-beam. Pressure and additional clamping systems available. Pole/beam installations require supplied mounting bar on flange.
ESTIMATED WEIGHT	900 lbs.
WARRANTY	Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.
ADDITIONAL OPTIONS MODEL NUMBER + ()	Hit/Error(HE), At Bat(AB), Pitch Count(PC), or Pitch Speed(PS) in place of the Graphics Area. Protective Lens Kit (PLK + Model Number). White, Green, Amber digits available (Red is standard).
AVAILABLE CONTROL CONSOLE (SOLD SEPARATELY)	MSC9000 (Multi-sport Desktop Console) Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep. Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option included. Internal rechargeable battery. Switch between multiple sports by removing and replacing the slip sheet.

PRODUCT SPECIFICATIONS
BA9280 OPTIONS

BA9280AB

21" AT BAT (AB) digits in place of graphics.

BALL	3	STRIKE	2	OUT	2	AT BAT				22				
	1	2	3	4	5	6	7	8	9	10		R	H	E
GUEST	0	3	0	1	0	0						4	6	
HOME	0	1	0	2	2							5	8	

BA9280HE

21" HIT/ERROR (HE) digits in place of graphics.

BALL	3	STRIKE	2	OUT	2					HIT/ERR	22			
	1	2	3	4	5	6	7	8	9	10		R	H	E
GUEST	0	3	0	1	0	0						4	6	
HOME	0	1	0	2	2							5	8	

BA9280PC

21" PITCH COUNT (PC) digits (up to 199) in place of graphics. Pitch count toggles between teams.

BALL	3	STRIKE	2	OUT	2					PITCH COUNT	101			
	1	2	3	4	5	6	7	8	9	10		R	H	E
GUEST	0	3	0	1	0	0						4	6	
HOME	0	1	0	2	2							5	8	

BA9280PS

21" PITCH SPEED (PS) digits (up to 199) in place of graphics.

BALL	3	STRIKE	2	OUT	2					PITCH SPEED	101	MPH			
	1	2	3	4	5	6	7	8	9	10		R	H	E	
GUEST	0	3	0	1	0	0						4	6		
HOME	0	1	0	2	2							5	8		

PLK + MODEL NUMBER

Protective Lenses Installed in front of each digit assembly.

