





OVERALL DIMENSION

3' high x 8' wide x 5" deep. Additional 1.5" mounting flange on top and bottom. Style available in other sizes.

CONSTRUCTION

Fabricated 20 and 22 GA Powder Coated Galvanneal. 2 Cabinet Installation.

INFORMATION

Timer (14"), Home & Guest Scores up to 99 (12"), Period (10"), Goal Light Indicators (2")

CAPTIONS

HOME, GUEST (5"), PERIOD (2.5"), GOAL (4")

HORN

Included 100dB internal horn. 110 dB external trumpet horn available, recommended to be wired at time of manufacture.

ELECTRONICS / DIGITS

100% solid state, microprocessor controlled system with locking connectors. Ultra bright, exposed Red and Amber LED digits.

SERVICING

Sign will be serviceable by removing the digit pan to access components.

COMMUNICATION

Radio communication is standard using a 2.4 GHz Frequency hopping spread spectrum transceiver. Hardwire optional on scoreboard, recommended to be installed at time of manufacture.

POWER REQUIREMENTS

120VAC, 2.6 Amp. Includes 6' power cable exiting the top left of the cabinet with standard grounded 3 prong connector. 20 Amp circuit recommended.

INSTALLATION

May be mounted to nearly any wall surface, no hardware supplied. Intended for dry locations.

ESTIMATED WEIGHT

133 lbs.

WARRANTY

Five year guarantee against defects in materials and workmanship. Factory repair service for parts in warranty. Union label. UL Certified.

ADDITIONAL OPTIONS

MODEL NUMBER + ()

Time Outs Left (TOL). Protective Lens Kit (PLK + Model Number). White, Green digits available (Red and Amber as shown is standard).

AVAILABLE CONTROL CONSOLE

MSC9000 (Multi-sport Desktop Console) Extruded Aluminum, high impact low profile microprocessor control console. 5" high x 10.25" wide x 9" deep. included. Internal rechargeable battery. Switch between multiple sports by

(SOLD SEPARATELY) Weight: 4.3 lbs. Radio (1600 ft) is standard, simultaneous hardwire option removing and replacing the slip sheet.

PRODUCT SPECIFICATIONS

HK9081 OPTIONS



